

 <p><b>帕斯特</b> Polymer Science Technology</p> <p>Shenzhen PST New Material Technology Co.,Ltd. 201,A District,Baoyuan Road Ba'an Shenzhen China</p>	<b>MSDS</b>  <b>( Material Safety Data Sheet )</b>	File No.	<b>PST—1001</b>
		Issue Data	<b>Aug, 8, 2013</b>
	<b>Adhesive Resin</b> <b>A1018/A1018T/A1028/F</b> <b>108</b>	Revised Data	
		Revised Item	
		Page	<b>1/ 3</b>

## SECTION 1. PRODUCT IDENTIFICATION

- |                    |                                  |
|--------------------|----------------------------------|
| 1) Product name    | Adhesive Resin A1018/A1018T/F108 |
| 2) Chemical family | THERMOPLASTIC POLYMER            |
| 3) Shipping name   | Plastic material                 |
| 4) Chemical name   | Thermoplastic polymer            |

## SECTION 2. COMPOSITION AND INGREDIENT INFORMARION

	<u>CAS No.</u>	<u>Wt %</u>
Polypropylene grafted - maleic anhydride	25722-45-6	80-99.9%
Maleic anhydride	108-31-6	<0.1 %

## SECTION 3. PHYSICAL AND CHEMICAL PROPERTIES

- |                                |                                |
|--------------------------------|--------------------------------|
| 1) Melting point               | 150-170℃                       |
| 2) Specific gravity            | 0.85-0.98 (H <sub>2</sub> O=1) |
| 3) Percent Volatile            | < 0.5%                         |
| 4) State and appearance        | Solid and pellet               |
| 5) Solubility in water % by WT | < 0.001                        |
| 6) Odor                        | Slight                         |

## SECTION 4. HAZARD IDENTIFICATION

### 1) EMERGNCY OVERVIEW

### 2) POTENTIAL HEALTH EFFECTS

1. Primary routes of Entry : Inhalation, skin and eye contact
2. Acute effects of exposure
  - a. Ingestion : No toxic symptoms reported, however, low toxicity by this route is expected based on biological activity of high molecular weight polyester polymers.
  - b. Inhalation : No toxic symptoms reported. Pellets are not considered an inhalation hazard.
  - c. Skin(contact) : No toxic symptoms reported. Molten material has the potential to cause thermal burns.
  - d. Eye(contact) : No toxic symptoms reported. Polymer particle may act as foreign body.

## SECTION 5. FIRST AID MEASURES



# **Adhesive Resin** **A1018/A1018T/** **A1028/F108**

File No.

Revised Data

Page

2/ 3

- 1) Ingestion : If significant quantity has been swallowed, give glass of water and induce vomiting. Seek medical attention.
- 2) Inhalation : Remove to fresh air. Seek medical attention if symptoms persist.
- 3) Skin(contact) : If molten polymer contacts skin. Cool rapidly with cold water. Seek medical attention.
- 4) Eye(contact) : Flush with plenty of water. Seek medical attention if symptoms persist.

## **SECTION 6. FIRE FIGHTING MEASURES**

- 1) Flash point (method used) :
- 2) Flammable limits in air % by volume :
- 3) Extinguishing media : Dry chemical, CO<sub>2</sub>, foam or water spray
- 4) Special fire-fighting procedures : Water and/ or dry chemical should not be used on Machinery. Self-contained breathing apparatus and personal protective equipment may be needed for large fires.
- 5) Unusual fire and explosion hazards : None known

## **SECTION 7. ACCIDENTAL RELEASE MEASURES**

- 1) Land Spill : Pellets are slippery. Scoop up material and put into suitable container for disposal as a non hazardous waste
- 2) Water Spill : This material will sink and is non-hazardous in water.
- 3) Accidental or Unplanned Releases : Clean area with vacuum or put into suitable container for disposal as a non hazardous waste.

## **SECTION 8. HANDLING AND STORAGE**

- 1) Handling : Wear long sleeves and gloves.  
Keep bags always closed and avoid pellets/bags from getting wet.
- 2) Storage : Keep bags in a well-ventilated place.  
Keep bags always closed and avoid pellets/bags from getting wet.

## **SECTION 9. EXPOSURE CONTROLS AND PERSONAL PROTECTION**

### 1) EXPOSURE CONTROLS

### 2) PERSONAL PROTECTION

#### a. Ventilation

Local exhaust mechanical : Recommended when appropriate to control employee exposure may not be adequate as the sole means to control employee exposure.

b. Respiratory protection : Approved respirators recommended when handling hot material.

c. Protective gloves : Recommend during melt processing

d. Eye protection : Safety glasses recommended.



**Adhesive Resin  
A1018/A1018T/A  
1028/F108**

File No.

Revised Data

Page

3/ 3

**SECTION 10. STABILITY AND REACTIVITY**

- 1) Stability : Chemically stable
- 2) Incompatibility(material to avoid) : Oxidizing materials can cause a reaction
- 3) Hazardous polymerization : Will not occur
- 4) Conditions to avoid : Do not heat above 290°C  
Avoid prolonged exposure to temperatures above 270°C
- 5) Hazard decomposition product : Major - Carbon dioxide, probably carbon monoxide  
Minor – Phosphoric anhydride

**SECTION 11. TOXICOLOGICAL INFORMATION**

**SECTION 12. ECCOLOGICAL INFORMATION**

This product is not classified as a hazardous.

**SECTION 13. WASTE DISPOSAL CONSIDERATION**

Transfer to an approved disposal area in accordance with regulations on industrial wasted disposal.

**SECTION 14. TRANSPORTATION INFORMATION**

**SECTION 15. REGULATORY INFORMATION**

Precautions to be taken in handling and storing storage in a cool dry place toxic substances controls act (TSCA) all the components of this product are listed on the TSCA inventory.

**SECTION 16. OTHER INFORMATION**

The information provided herein is based on our current knowledge and experience.  
All materials may present unknown health hazards and should be used with caution.  
Final responsibility lies in user's determination although the MSDS is described herein.  
We cannot guarantee that these are the only hazards which exist.